

STARVIEW™

ASP & ASP/IR SERIES AUTOMATIC SKIN PACKAGING MACHINES



ASP Series with automatic overhead out-feed (upper left) and ASP/IR Series with standard manual out-feed table (lower right).

- ★ Standard sizes 18 x 24" through 36" x 48" offered
- ★ Use for retail carded packaging or shipping containment
- ★ PLC machine control with touch screen operator interface panel
- ★ Moving template in-feed and manual out-feed tables standard
- ★ Impulse hot wire cut-off standard
- ★ Optional automatic out-feed available

Description

Starview's ASP & ASP/IR Series skin packaging machines are designed for low to medium volume applications. ASP machines incorporate a stationary heating system with instant on/off heaters. ASP/IR models incorporate an automatic retractable radiant heater panel system, controlled by percentage controllers for precise heat distribution. All ASP & ASP/IR skin packaging machines have PLC timer control for precision repeatability and an accurate turbine regulator. An automatic in-feed table with traveling template loader, out-feed table and impulse type hot wire cut-off are all standard.

Starview's ASP & ASP/IR Series skin packaging machines can be equipped with a three-stage vacuum system for products with complex shapes. An optional automatic overhead out-feed system is offered. The PLC can be used to advance a customer furnished conveyor to remove finished skin packages from the work area.

SPECIFICATIONS

Model	ASP-1824	ASP/IR-1824	ASP-2430	ASP/IR-2430
Max card size:	18" x 24"	18 x 24"	24" x 30"	24" x 30"
Max product ht:	6"	6"	6"	6"
Heating system:	Quartz impulse	Radiant panel	Quartz impulse	Radiant panel
Avg. cycle speed:	15-60 seconds	15-45 seconds	15-60 seconds	15-45 seconds
Approximate size:	110W x 39D x 63"H	110W x 65D x 69"H	116W x 42D x 63"H	133W x 76D x 69"H
Approximate wt:	600 LB.	700 LB.	700 LB.	800 LB.
Model	ASP-2436	ASP/IR-2436	ASP-3036	ASP/IR-3036
Max card size:	24" x 36"	24" x 36"	30" x 36"	30" x 36"
Max product ht:	6"	6"	6"	6"
Heating system:	Quartz impulse	Radiant panel	Quartz impulse	Radiant panel
Avg. cycle speed:	15-60 seconds	15-45 seconds	15-60 seconds	15-45 seconds
Approximate size:	151W x 42D x 63"H	151W x 76D x 69"H	151W x 48D x 63"H	151W x 93D x 69"H
Approximate wt:	800 LB.	900 LB.	1,000 LB.	1,100 LB.
Model	ASP-3048	ASP/IR-3048	ASP-3648	ASP/IR-3648
Max card size:	30" x 48"	30" x 48"	36" x 48"	36" x 48"
Max product ht:	6"	6"	6"	6"
Heating system:	Quartz impulse	Radiant panel	Quartz impulse	Radiant panel
Avg. cycle speed:	15-60 seconds	15-45 seconds	15-60 seconds	15-45 seconds
Approximate size:	163W x 48D x 63"H	163W x 93D x 69"H	163W x 54D x 63"H	163W x 100D x 69"H
Approximate wt:	1,300 LB.	1,400 LB.	1,400 LB.	1,500 LB.

Specifications and model availability are subject to change without notice.

Please request specific model quotations for complete pricing, specifications and options from your local distributor. Feel free to contact Starview to obtain the contact information for the authorized distributor in your area.



Starview Packaging Machinery, Inc.
 9325 TransCanada Highway
 St. Laurent, Quebec H4S 1V3
www.starview.net

Toll Free: 888-278-5555
 Tel: 514-920-0100
 Fax: 514-920-0092
 Email: sales@starview.net



Manufacturers of a full line of Blister Packaging Machines, Clamshell Sealing Machines, Skin Packaging Machines, Food Packaging Machines, Vacuum and Pressure Formers, Die Cutting Machines and related tooling.

Copyright 2007 Starview Packaging Machinery, Inc.

