

M.J. MAILLIS

WULFTEC.com

AUTOMATIC ROTARY ARM STRETCH WRAPPERS

WHY GO AUTOMATIC?

Automatic stretch wrappers are designed to maximize throughput and efficiency. They take care of everything; all you need to do is change the roll of film. An automatic stretch wrapper will save you significant time and money.

BENEFITS OF A ROTARY ARM

Rotary arm stretch wrappers are extremely versatile and can wrap almost anything. Since the load remains stationary, they are ideal for wrapping very light, very heavy, tall or unstable loads. They are also great in wash-down applications.

THE WULFTEC ADVANTAGE :

- Allen Bradley PLC for more flexibility
- AC variable frequency drives and motors
- Heavy-duty steel construction
- NO-THREAD® powered pre-stretch carriage
- Quick disconnects throughout for ease of installation and maintenance
- Superior warranties

- * 4-YEARS UNLIMITED CYCLE WARRANTY (3-YEAR ON THE WCRT-175 & WCRT-200)
- * 10-YEAR WARRANTY ON THE RING-GEAR
- * 10-YEAR WARRANTY ON STRUCTURAL FRAME
- * LIFETIME WARRANTY ON PRE-STRETCH ROLLERS' BLUE COMPOUND



WCRT-175

Self-Supporting 3-Legged Model
Up to 60 loads per hour*
Load size:
Min.: 36"W x 36"L x 10"H
Max.: 48"W x 48"L x 80"H
Weight capacity: 5,000 lbs
(6,000 lbs optional)
Machine dimensions:
141"W X 138"L X 140"H
15 RPM variable speed



WRTA-100

Column-Mounted Model
Up to 50 loads per hour*
Load size:
Min.: 36"W x 36"L x 30"H
Max.: 56"W x 56"L x 80"H
Machine dimensions:
130"W X 135½"L X 119⅞"H
12 RPM variable speed



WRTA-150

Floor-Mounted Model
Up to 50 loads per hour*
Load size:
Min.: 36"W x 36"L x 30"H
Max.: 56"W x 56"L x 80"H
Machine dimensions:
130"W X 165½"L X 117½"H
12 RPM variable speed



WRTA-175

Self-Supporting 3-Legged Model
Up to 50 loads per hour*
Load size:
Min.: 36"W x 36"L x 30"H
Max.: 56"W x 56"L x 80"H
Machine dimensions:
130"W X 146"L X 122"H
12 RPM variable speed



WRTA-200

Self-Supporting 4-Legged Model
Up to 50 loads per hour*
Load size:
Min.: 36"W x 36"L x 30"H
Max.: 56"W x 56"L x 80"H
Machine dimensions:
130"W X 147½"L X 117½"H
12 RPM variable speed



WCRT-200

Self-Supporting 4-Legged Model
Up to 100 loads per hour*
Load size:
Min.: 36"W x 36"L x 10"H
Max.: 48"W x 48"L x 80"H
Weight capacity: 5,000 lbs
(6,000 lbs optional)
Machine dimensions:
148"W X 138"L X 140"H
17 RPM variable speed



EXCLUSIVE ELEMENTS

NO-THREAD® POWERED PRE-STRETCH CARRIAGE 50-300% PRE-STRETCH

- SAFE AND FAST LOADING PROCESS
- LEXAN GATE SAFETY COVER
- DOUBLE LATCH SAFETY GATE LOCK
- VIRTUALLY SILENT OPERATION
- EXCELLENT FILM STRETCHING PERFORMANCE
- MAINTENANCE FREE AC MOTOR WITH VARIABLE FREQUENCY DRIVE FOR CORNER COMPENSATION
- LIFETIME WARRANTY ON PRE-STRETCH ROLLERS' BLUE COMPOUND



ALLEN BRADLEY - PLC

- PROGRAMMING FLEXIBILITY
- RELIABLE
- ACCESSIBLE VIA MODEM*
- NON-PROPRIETARY
- EASY TROUBLE SHOOTING

*DEPENDENT ON MODEL



ALLEN BRADLEY VARIABLE FREQUENCY DRIVES

- EASY SET-UP
- ACCURATE SPEED CONTROL
- EASY DIGITAL READOUT
- EXCELLENT REPEATABILITY OF SETTINGS
- MAINTENANCE FREE



* Production rate based on load size and configuration.

WE FEAR NO PACKAGING CHALLENGE
www.wulftec.com

