

WE FEAR NO PACKAGING CHALLENGE

**M.J. MAILLIS**

WWW.WULFTEC.COM

**WULFTEC®**

**TECHNICAL SPECIFICATIONS**

	<b>WRT-100</b>	<b>WRT-150</b>	<b>WRT-175</b>	<b>WRT-200</b>
<b>PRODUCTION RATE*</b>	- Up to 50 loads per hour	- Up to 50 loads per hour	- Up to 50 loads per hour	- Up to 50 loads per hour
<b>MAX LOAD WEIGHT</b>	- Unlimited	- Unlimited	- Unlimited	- Unlimited
<b>MIN LOAD SIZE</b>	- 36"W x 36"L x 10"H	- 36"W x 36"L x 10"H	- 36"W x 36"L x 10"H	- 36"W x 36"L x 10"H
<b>MAX LOAD SIZE</b>	- 56"W x 56"L x 80"H	- 56"W x 56"L x 80"H	- 56"W x 56"L x 80"H	- 56"W x 56"L x 80"H
<b>MACHINE DIMENSIONS**</b>	- 130"W x 135½"L x 119½"H	- 130"W x 165½"L x 117½"H	- 130"W x 138"L x 122"H	- 130"W x 147¾"L x 117½"H
<b>APPROXIMATE SHIPPING WEIGHT</b>	- 1,850 lbs.	- 2,050 lbs.	- 2,200 lbs.	- 2,450 lbs.
<b>ELECTRICAL REQUIREMENTS</b>	- 120V/1/60 15A	- 120V/1/60 15A	- 120V/1/60 15A	- 120V/1/60 15A
<b>CONTROLS</b>	- NEMA 4/12 control cabinet with quick disconnect - Separate up and down carriage speeds - Separate top and bottom wrap selectors - Top cover pause switch - Spiral up/down - and more...	- NEMA 4/12 control cabinet with quick disconnect - Separate up and down carriage speeds - Separate top and bottom wrap selectors - Top cover pause switch - Spiral up/down - and more...	- NEMA 4/12 control cabinet with quick disconnect - Separate up and down carriage speeds - Separate top and bottom wrap selectors - Top cover pause switch - Spiral up/down - and more...	- NEMA 4/12 control cabinet with quick disconnect - Separate up and down carriage speeds - Separate top and bottom wrap selectors - Top cover pause switch - Spiral up/down - and more...
<b>FILM DELIVERY SYSTEM</b>	- 20" NO-THREAD® powered pre-stretch carriage (angled carriage to wrap lower) - 50-300% pre-stretch - 1 HP AC motor with variable frequency drive	- 20" NO-THREAD® powered pre-stretch carriage (angled carriage to wrap lower) - 50-300% pre-stretch - 1 HP AC motor with variable frequency drive	- 20" NO-THREAD® powered pre-stretch carriage (angled carriage to wrap lower) - 50-300% pre-stretch - 1 HP AC motor with variable frequency drive	- 20" NO-THREAD® powered pre-stretch carriage (angled carriage to wrap lower) - 50-300% pre-stretch - 1 HP AC motor with variable frequency drive
<b>ROTARY ARM DRIVE</b>	- 25" ring gear bearing drive/support - 12 RPM variable speed - ¾ HP AC motor with variable frequency drive	- 25" ring gear bearing drive/support - 12 RPM variable speed - ¾ HP AC motor with variable frequency drive	- 25" ring gear bearing drive/support - 12 RPM variable speed - ¾ HP AC motor with variable frequency drive	- 25" ring gear bearing drive/support - 12 RPM variable speed - ¾ HP AC motor with variable frequency drive
<b>STRUCTURE</b>	- Heavy-duty structural steel construction (column mount)	- Heavy-duty structural steel construction (floor mount, 1 leg)	- Heavy-duty structural steel construction (floor mount, 3 legs)	- Heavy-duty structural steel construction (floor mount, 4 legs)
<b>WARRANTY</b>	- 3-year unlimited cycle warranty - 10-year warranty on steel structure - 10-year warranty on 25" ring gear bearings - Lifetime warranty on pre-stretch rollers' blue compound	- 3-year unlimited cycle warranty - 10-year warranty on steel structure - 10-year warranty on 25" ring gear bearings - Lifetime warranty on pre-stretch rollers' blue compound	- 3-year unlimited cycle warranty - 10-year warranty on steel structure - 10-year warranty on 25" ring gear bearings - Lifetime warranty on pre-stretch rollers' blue compound	- 3-year unlimited cycle warranty - 10-year warranty on steel structure - 10-year warranty on 25" ring gear bearings - Lifetime warranty on pre-stretch rollers' blue compound

Working closely with customers around the world, Wulftec is continuously developing and expanding its complete line of automatic and semi-automatic stretch wrap machines - turntables, rotary arms and horizontals.

Superior safety features are engineered into every Wulftec® machine. Wulftec's exceptional performance characteristics ensure reliability even in the harshest working conditions.

\* PRODUCTION RATE BASED ON LOAD SIZE AND CONFIGURATION  
\*\* OVERALL DIMENSIONS OF THE MACHINE IN OPERATION

ALL MACHINE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE  
NOMINAL DIMENSIONS SHOWN

**M.J. MAILLIS**

**WULFTEC®**

**WULFTEC® STRETCH WRAPPERS  
SEMI-AUTOMATIC ROTARY ARMS**

**NON-CONVEYORIZED**

- WRT-100**
- WRT-150**
- WRT-175**
- WRT-200**



**WHATEVER THE NEED FOR  
A STRETCH WRAPPING SYSTEM,**

**WULFTEC HAS AN ECONOMICAL, HEAVY DUTY,  
OR CUSTOM BUILT SOLUTION TO MEET YOUR  
SPECIFIC REQUIREMENTS.**



**CHOOSE THE OPTIONS YOU WANT...  
...GET THE RUGGED EFFICIENCY YOU NEED!**

WE FEAR NO PACKAGING CHALLENGE

WWW.WULFTEC.COM

## WHY CHOOSE WULFTEC?

SUPERIOR SAFETY FEATURES ARE ENGINEERED INTO EVERY WULFTEC® MACHINE. WULFTEC'S EXCEPTIONAL PERFORMANCE CHARACTERISTICS ENSURE RELIABILITY EVEN IN THE HARSHTEST WORKING CONDITIONS.

### BENEFITS OF A ROTARY ARM

Rotary arm models, compared to turntable models, are designed for increased flexibility and for unique load shapes or weights. The rotary arm rotates around a stationary load; a safe, highly effective way of wrapping very light, tall, heavy or unstable loads.

### FEATURING



AC variable frequency drives and motors for safe, reliable performance and minimal maintenance



20" NO-THREAD® powered pre-stretch carriage for quick, easy and safe film loading; 50% to 300% pre-stretch for optimal film use and reduced costs



25" Ring GEAR Bearing, with Pinion GEAR Drive for unbeatable strength and durability



Dual chain carriage lifts  
Dual chain system improves machine security and ensures stable lifting thus eliminating vibrations

- Dual structural steel boom  
- Wraps 2" from floor - Guaranteeing a secure load

## WE'LL KEEP YOU RUNNING AT PEAK SPEED!



**WRT-100**  
Column-Mounted Model

#### ALL WULFTEC® SEMI-AUTOMATIC ROTARY ARM MACHINES FEATURE COMMON BENEFITS:

- Up to 50 loads per hour
- 20" NO-THREAD® powered pre-stretch carriage with 50-300% pre-stretch
- 25" ring gear bearing drive/support
- 12 RPM variable speed
- Unlimited load weight capacity
- Heavy-duty structural steel construction
- Nema 4/12 control cabinets
  - superior protection against water and dust
  - quick disconnect for easy and fast installation

**WRT-150**  
Floor-Mounted Model



**WRT-175**  
Self-Supporting Three-Legged Model

#### MAIN PERFORMANCE FEATURES:

- Separate up and down carriage speeds
- Separate top and bottom wrap selectors (0-9)
  - wrap patterns can be set for optimum load containment
- Top cover pause switch
  - top sheet can be manually inserted for splash proof protection

**WRT-200**  
Self-Supporting Four-Legged Model



### THE WULFTEC ADVANTAGE:

Allen Bradley PLC for more flexibility  
AC variable frequency drives and motors  
Heavy-duty steel construction  
NO-THREAD® powered pre-stretch carriage  
Superior warranties:



- LIFETIME WARRANTY ON PRE-STRETCH ROLLERS' BLUE COMPOUND
- 10-YEAR WARRANTY ON STRUCTURAL STEEL FRAME
- 10-YEAR WARRANTY ON RING GEAR
- 3-YEAR UNLIMITED CYCLE WARRANTY

### WHY COMPROMISE? CUSTOMIZE!

#### OUR MOST POPULAR OPTIONS:

**30" NO-THREAD® POWERED PRE-STRETCH CARRIAGE:** LARGER WEB MEANS YOU'LL WRAP FASTER AND USE LESS FILM

**ROPING WITH PNEUMATIC CYLINDER:** THE CARRIAGE MOUNTED ROPING DEVICE TURNS THE FILM TO A ROPE BY TWISTING IT INTO A STRONG CABLE THAT WILL ATTACH THE LOAD, USING A SPECIAL PATTERN, TO THE WINGS OF THE PALLET

**WRAP HEIGHT EXTENSION:** WRAPS LOADS EXCEEDING 80" IN HEIGHT

**DARK LOAD PHOTOEYE:** WRAPS DARK OR SHINY LOADS THAT REFLECT LIGHT

**ROTATION SPEED:** INCREASES SPEED SO YOU'LL WRAP MORE IN LESS TIME

### NEED HELP CHOOSING?

Call us at  
1 877 WULFTEC (985-3832)  
or contact your  
Wulftec Distributor