STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD. $\Delta | |$



SMART DESIGNS COME FROM SMART SOLUTIONS.



NESTAFLEX SKATE WHEEL CONVEYOR GRAVIT



4-Point Leg Connection

The 275 features ALL BOLTED CONSTRUCTION and is a heavy duty, gravity conveyor that features DOUBLE welded cross braces and reinforced inner legs for added support. The

ALL-STEEL reinforced leg and frame design provides the strength necessary to handle heavy cartons and industrial atmospheres.

The ALL-STEEL construction provides unmatched structural integrity, whether the conveyor is extended, compacted or configured in simple or compound curves. Adjustable inner legs vary height to achieve gravity flow. The NESTAFLEX 275 has a proven track record in the manufacturing field and is the choice for



Adjustable Height Legs



Caster with Br



medium to high volume shipping and receiving departments. Call us today to learn

more at 800.669.1501 or visit our website at www.flexmh.com

Flexible Side Rails

CONVEYOR OPTIONS



Impact Conveyor



Swing Gate

Flexible Material Handling



ALL STEEL CONSTRUCTION. THE STRONGEST CONVEYORS IN THE WORLD.

SMART DESIGNS COME FROM SMART SOLUTIONS.

SPECIFICATIONS

18" WIDTHS			24" WIDTHS		30" WIDTHS			LENGTH ADJUSTMENTS WITH 5 1/4" AXLE CENTERS			
Model 275	Skate Wheels Per Axle		Model 275	Skate Wheels Per Axle		Model 275	Skate Wheels Per Axle		Contracted/ Extended	Leg Sets Per Unit	Bed Sections Per Unit
27518008	6		27524008	9		27530008	12		2'7"-8'6"	3	2
27518012	6		27524012	9		27530012	12		3′7″-12′2″	4	3
27518016	6		27524016	9		27530016	12		4′ 8″ - 15′ 10″	5	4
27518020	6		27524020	9		27530020	12		5′8″-19′6″	6	5
27518024	6		27524024	9		27530024	12		6′8″-23′2″	7	6
27518028	6		27524028	9		27530028	12		8′2″-28′0″	8	7
27518032	6		27524032	9		27530032	12		9′2″-31′8″	9	8
27518036	6		27524036	9		27530036	12		10′3″-35′4″	10	9
27518040	6		27524040	9		27530040	12		12' 1" - 41' 10"	12	11
27518044	6		27524044	9		27530044	12		13′1″-45′6″	13	12
27518048	6		27524048	9		27530048	12		14′4″-49′5″	14	13
27518052	6		27524052	9		27530052	12		15′4″-53′1″	15	14
27518056	6		27524056	9		27530056	12		16′5″-56′9″	16	15
27518060	6		27524060	9		27530060	12		17′5″-60′5″	17	16

Also available in 36" widths.

NESTAFLEX 275 STANDARD FEATURES AND OPTIONS



SKATE WHEEL OPTIONS



N-Red Nylon



P-Black Polymer



S-Steel

CONSTRUCTION

All-steel BOLTED construction.

CONVEYOR FORMATS

Available in 18", 24" and 30" widths. 36" available upon request. Lengths can be tailored to your specific application.

SKATE WHEEL OPTIONS

N-Red Nylon with nylon bushing for high-impact, short conveyors runs.

P-Black Polymer with 7 steel ball bearings in a captive race provides superior wheel rotation.

S-Steel skate wheel with steel ball bearings for impact resistant, moderate to high volume usage.

HEIGHT ADJUSTMENT

Standard adjustable heights from 28" to 36". Other height options available.

LEGS

Zinc plated 1 1/8 O.D. 12 gauge steel tubing with adjustable reinforced inner leg and double cross braces. Incremental height marks are provided on outer leg to facilitate uniform height adjustment. Four point bolted leg connection to skate wheel axles and side links.

HEAVY DUTY CASTERS

Standard 5" x 1 1/2" casters with heavy duty stem. Casters with swivel/wheel lock pedal brakes are provided on the first and last legs. 6" x 2" casters available for added strength and mobility.

Flexible Material Handling

SMART SOLUTIONS™ ww.flexmh.com 800-669-1501

S	IDE	LINKS

Conveyor side links are made of 7 gauge steel and feature bolted construction.

COUPLERS

Couplers are standard. Optional universal connectors are available to couple to other extendable conveyor brands.

BOX STOP/HANDLE

Standard retractable package stop serves also as an ergonomic handle.

AXLES

5/16" diameter axles. Standard axle centers are 5 1/4", 4" and 3" are available for smaller cartons.

WARRANTY

Two year factory warranty.