



CASE ERECTOR

MASTER SERIES MCE-2210

The MCE-2210 Series is unrivaled in terms of quality, performance, reliability and usability. The Master MCE-2210 Series is a case erector and bottom flap hot melt glue/tape sealer for assembling corrugated cases. This system automatically selects, erects, and seals the bottom flaps of RSC and HSC cases at speeds up to 16 per minute.

The MCE-2210 uses a dual opposing vacuum case opening system to ensure each case is opened positively from both sides. This overcomes problems associated with stiff board and glue migration from the manufacturer's joint. RSC or HCS cases will run without a problem.

The MCE-2210 unique handling system works well with normal RSC or HCS cases. No tapered flaps are required.

- Positive dual opposing vacuum case opening
- Compact footprint
- Clear access
- Robust construction
- Quick size change



Operator Controls



Exit Belt conveyor



Stack Light

FEATURES

- Heavy-duty rugged construction designed for high durability and around-the-clock operation
- Powder coat finish that provides a durable scratch resistant surface and prevents corrosion
- A modern and versatile solution for the erection of typical commercial quality cases
- Compact footprint allows automation in areas not normally suited for installation of large machines
- Simple mechanical operation and clear access for easy size change, cleaning and maintenance
- High quality components, housed in a robust, computer designed chassis allow for minimal servicing. Designed for the rigours of typical End-of-Line packaging environments
- Operator friendly, adjusts in minutes. Simple controls mean that the machine is available for the maximum amount of time

OPTIONS

- Stainless Steel Construction
- Optional Kit - comprises message display unit, low hopper sensing, low tape/glue sensing, no-tape sensing and visual/audible failure alarm for simple and fast machine status information
- Up to 20 cases per minute with reduced size range

SPECIFICATIONS

Speed

- Up to 16 cases per minute

Power Requirements

- Electrical: 380-415VAC, 3Ph, 50Hz, 0.5kW (Type 221)
Electrical: 230VAC, 3Ph, 50Hz, 4.0kW (Type 223)
- Pneumatic: 80 psi

Case Sizes (open)*

- Length: 8"-19 1/2"
- Width: 6"-15 3/4"
- Height: 7"-23.5"

* The 221 case erector seals cases with self-adhesive tape. The 223 case erector seals cases with hot melt glue.

Tape Sizes

- Standard: up to 2" wide
- Optional: up to 3" wide

