

WE FEAR NO PACKAGING CHALLENGE

M.J. MAILLIS

WWW.WULFTEC.COM

WULFTEC®

TECHNICAL SPECIFICATIONS

NON-CONVEYORIZED MODELS

CONVEYORIZED MODELS

	WRTA- 100 / 150 / 175 / 200	WCRT- 175 / 200
PRODUCTION RATE*	- Up to 50 loads per hour	- WCRT-175: Up to 60 loads per hour - WCRT-200: Up to 100 loads per hour
LOAD WEIGHT	- Unlimited	- 4,000 lbs. (6,000 lbs. option)
MIN LOAD SIZE	- Min.: 36"W x 36"L x 30"H	- Min.: 36"W x 36"L x 10"H
MAX LOAD SIZE	- Max.: 56"W x 56"L x 80"H	- Max.: 48"W x 48"L x 80"H
MACHINE DIMENSIONS**	- WRTA-100: 130"W x 135½"L x 119⅞"H - WRTA-150: 130"W x 165½"L x 117½"H - WRTA-175: 130"W x 146"L x 122"H - WRTA-200: 130"W x 147½"L x 117½"H	- WCRT-175: 141"W x 138"L x 140"H - WCRT-200: 148"W x 138"L x 140"H
APPROXIMATE SHIPPING WEIGHT	- WRTA-100: 2,300 lbs. - WRTA-150: 2,500 lbs. - WRTA-175: 2,500 lbs. - WRTA-200: 2,800 lbs.	- WCRT-175: 3,700 lbs. (standard system) - WCRT-200: 4,500 lbs. (standard system)
ELECTRICAL REQUIREMENTS***	- 120V/1/60 15A	- 230V/3/60 20A
PNEUMATIC REQUIREMENTS	- 3 CFM @ 80 PSI comes with FR (Filter, Regulator)	- 3 CFM @ 80 PSI comes with FR (Filter, Regulator)
CONTROLS	- NEMA 4/12 control cabinet with quick disconnect - Separate up and down carriage speeds - Separate top and bottom wrap selectors - Top cover pause switch - Pull cord with 40' of cable - Manual carriage up/down switch - Manual arm rotation - Reinforce wrap	- NEMA 12 control cabinet with quick disconnect - Separate up and down carriage speeds - Separate top and bottom wrap selection - Touch screen operator interface - Intuitive alarm diagnostics - On-screen wrapping performance analysis - On-screen maintenance program and instructions
FILM DELIVERY SYSTEM	- 20" NO-THREAD® powered pre-stretch carriage (angled carriage to wrap lower) - 50-300% pre-stretch - 1 HP AC motor with variable frequency drive for corner compensation	- 20" NO-THREAD® powered pre-stretch carriage (angled carriage to wrap lower) - 50-300% pre-stretch - 1 HP AC motor with variable frequency drive for corner compensation
FILM TAIL TREATMENT	- Automatic film clamping - Pulsed-controlled cutter - Film alignment arm and brush on film treatment	- Automatic film clamping - Pulsed-controlled cutter - Film alignment arm and brush on film treatment
ROTARY ARM DRIVE	- ¾ HP AC motor with variable frequency drive - 25" Ring GEAR Bearing, with Pinion GEAR Drive - 12 RPM variable speed	- 1 HP AC motor with variable frequency drive - 25" Ring GEAR Bearing, with Pinion GEAR Drive - WCRT-175: 15 RPM - WCRT-200: 17 RPM (other speeds available)
CONVEYORS	- Not applicable	- 11'6" long powered process conveyor - Heavy-duty cast iron flange mounted bearings - 2½" dia. rollers on 3" centers - 52" between frame rails
STRUCTURE	- Heavy-duty structural steel construction	- Heavy-duty structural steel construction
WARRANTY	- 3-year unlimited cycle warranty - 10-year warranty on steel structure - 10-year warranty on 25" ring gear bearings - Lifetime warranty on pre-stretch rollers' blue compound	- 3-year unlimited cycle warranty - 10-year warranty on steel structure - 10-year warranty on 25" ring gear bearings - Lifetime warranty on pre-stretch rollers' blue compound

*PRODUCTION RATE BASED ON LOAD SIZE AND CONFIGURATION

**OVERALL DIMENSIONS OF MACHINE IN OPERATION

***OTHER VOLTAGES AVAILABLE UPON REQUEST

ALL MACHINE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE
ALL CONVEYORIZED MODELS REQUIRE SAFETY FENCING
NOMINAL DIMENSIONS SHOWN

M.J. MAILLIS

WULFTEC®

**WULFTEC® STRETCH WRAPPERS
AUTOMATIC ROTARY ARMS**

NON-CONVEYORIZED

WRTA-100

WRTA-150

WRTA-175

WRTA-200

CONVEYORIZED

WCRT-175

WCRT-200



WHATEVER THE NEED FOR A STRETCH WRAPPING SYSTEM,

WULFTEC HAS AN ECONOMY, HEAVY DUTY OR CUSTOM BUILT SOLUTION TO

MEET YOUR SPECIFIC REQUIREMENTS. CHOOSE THE OPTIONS YOU WANT...

...GET THE RUGGED EFFICIENCY YOU NEED!

WE FEAR NO PACKAGING CHALLENGE

WWW.WULFTEC.COM

WHY GO AUTOMATIC?

AUTOMATIC STRETCH WRAPPERS ARE DESIGNED TO MAXIMIZE THROUGHPUT AND EFFICIENCY. THEY TAKE CARE OF EVERYTHING; ALL YOU NEED TO DO IS CHANGE THE ROLL OF FILM. AN AUTOMATIC STRETCH WRAPPER WILL SAVE YOU SIGNIFICANT TIME AND MONEY.

BENEFITS OF A ROTARY ARM

Rotary arm stretch wrappers are extremely versatile and can wrap almost anything. Since the load remains stationary, they are ideal for wrapping very light, very heavy, tall or unstable loads. They are also great in wash-down applications.

FEATURING



Allen Bradley PLC with touch screen panel for a wide range of options and program changes (optional on WRTA models)



AC variable frequency drives and motors for safe, reliable performance and minimal maintenance



20" NO-THREAD® powered pre-stretch carriage for quick, easy and safe film loading; 50% to 300% pre-stretch for optimal film use and reduced costs



Cut & Wipe film treatment system eliminates the need to attach and cut film, minimizing operator involvement and guaranteeing a tight wrap with no film tail for worry-free transport



25" Ring GEAR Bearing, with Pinion GEAR Drive for unbeatable strength and durability

- Dual chain carriage lift and dual structural steel boom
- Wraps 2" from conveyor or floor

WE'LL KEEP YOU RUNNING AT PEAK SPEED!

NON-CONVEYORIZED ROTARY ARMS

CONVEYORIZED ROTARY ARMS

ALL THE BENEFITS OF AUTOMATION...

...AT AN AFFORDABLE PRICE

WRTA-100

Column-Mounted Model



WRTA-150

Floor-Mounted Model



WRTA-175

Self-Supporting Three-Legged Model



- Unlimited load weight capacity
- Up to 50 loads per hour

WRTA-200

Self-Supporting Four-Legged Model



WCRT-175

Self-Supporting Three-Legged Model

- Optional elevating clamp for banding, separate double stack and one-way wrapping mode (WCRT-200)
- Easy access to all components for trouble-free maintenance
- 4,000 lbs. load weight capacity (6,000 lbs. option)
- Up to 100 loads per hour (WCRT-200)



WCRT-200

Self-Supporting Four-Legged Model

THE WULFTEC ADVANTAGE:

Allen Bradley PLC for more flexibility
AC variable frequency drives and motors
Heavy-duty steel construction
NO-THREAD® powered pre-stretch carriage
Superior warranties:



- LIFETIME WARRANTY ON PRE-STRETCH ROLLERS' BLUE COMPOUND
- 10-YEAR WARRANTY ON STRUCTURAL STEEL FRAME
- 10-YEAR WARRANTY ON RING GEAR
- 3-YEAR UNLIMITED CYCLE WARRANTY

WHY COMPROMISE? CUSTOMIZE!

OUR MOST POPULAR OPTIONS:

30" NO-THREAD® POWERED PRE-STRETCH CARRIAGE: LARGER WEB MEANS YOU'LL WRAP FASTER AND USE LESS FILM

POP-UP DEVICE: LIFTS THE LOAD SO THE FILM CAN GO UNDER THE PALLET, SECURING THE LOAD RIGHT TO THE PALLET (WCRT-175 & WCRT-200 MODELS)

WRAP HEIGHT EXTENSION: WRAPS LOADS EXCEEDING 80" IN HEIGHT

DARK LOAD PHOTOEYE: WRAPS DARK OR SHINY LOADS THAT REFLECT LIGHT

ROTATION SPEED: INCREASES SPEED SO YOU'LL WRAP MORE IN LESS TIME

TOP PLATEN: STABILIZES LIGHT AND UNSTABLE LOADS

TOP SHEET DISPENSERS: APPLIES A PROTECTIVE PLASTIC SHEET ON TOP OF THE LOAD

-INCYCLE TOP SHEET DISPENSER PROTECTS AGAINST WATER INGRESS (WCRT-200 ONLY)

-INLINE TOP SHEET DISPENSER PROTECTS AGAINST DUST (WCRT-175 & WCRT-200 MODELS)